STEFAN BOSSE^{1,2*} DIRK LEHMHUS³

¹Fachbereich Mathematik und Informatik

Universität Bremen

sbosse@uni-bremen.de www.edu-9.de

²Fakultät Maschinenbau

Universität Siegen

³Fraunhofer IFAM, Bremen







CONTENT



02

03

Introduction

Image Data Measuring Technologies Features and Challenges

Methods (1)

Aluminum Die Casted Plates X-ray Radiography Image Data Feature Marking (Pores)

Methods (2)

Fibre Metal Lamninate Plates X-ray CT Image Data Feature Marking (Damages, Defects)

IFAM



Results (1)

CNN Pore Detector In X-ray Radiograpy Images Modelling of Pores & Simulation



Results (2)

CNN/LSTM Anomaly Detector in 3D X-ray CT Data Modelling of Impact Damages



Conclusions

Identified Challenges What is possible? To do.. Outlook, Roadmap

INTRODUCTION: TOPICS AND FOCUS



INTRODUCTION: NON-DESTRUCTIVE TESTING

- **Non-destructive testing** (NDT) of metal-based structures can exploit different imaging methods, mainly:
 - X-ray Radiography (single projection) and Computer Tomography (CT, multiprojection)
 - Guided **Ultrasonic Waves** (GUW) and Ultrasonic Sonography
- Detection of hidden damages, defects, and impurities (e.g., pores) is still a challenge!



Primary Goal. Automated Damage, Defect, and Impurity Detection in materials and structures including composites using single X-ray projection images (from Low-Q/Mid-Q devices) and data-driven feature marking models (Convolutional Neural Networks).

INTRODUCTION: EXPERIMENTS AND GOALS

Different specimens, structure geometries, materials, and defects are considered in this work! They pose different coincidence between material and image features.

- **1**. Homogeneous Aluminum Die Casting Plates (150x40 mm) with pore defects
- 2. Composite Fibre Metal Laminate plates (FML, aluminum and PREG layers, 50 x 50 mm) with impact damages posing layer delaminations, deformation, cracks, and kissing bond defects.



Secondary Goal. Migration from laboratory (High-Q/Mid-Q) to in-field (Low-Q) measuring techniques and devices.



INTRODUCTION: AUTOMATED FEATURE DETECTION

- Automated feature detection and marking in measuring images can occur on different levels:
 - Region-of-Interest Search
 - Feature marking and Maps
 - Damage and defect classification
 - Damage and defect localization
 - Global statistical aggregates (e.g., pore density, distribution)
- Either classical numerical and model-based algorithms (e.g., edge detection using a Soebel filter or Canny detectors) or data-driven models are used for feature marking ("Machine Learning")



Jniversität

Bremen

Data-driven models require data! Data must contain a sufficient statistical variance and distribution of features to be detected. That's the first issue with most engineering data! Additionally, supervised data modelling requires accurately labelled strong feature examples, commonly not available, and being the second issue and downfall in data-driven modelling.

DATA-DRIVEN NDT FRAMEWORK



🜌 Fraunhofer

IFAM

Bremen

PRINCIPLE CONCEPT (1) : X-RAY RADIOGRAPHY



Universität Bremen Fraunhofer

PRINCIPLE CONCEPT (2): X-RAY COMPUTER TOMOGRAPHY





IFAM



11

DEVICE CLASSES	High-Q	Mid-Q	Low-Q
Single Projection	I		\bigcirc
Mult-Projection (Rotation)	O	~	
X-ray Tube Focal Diameter	5µm	0.8mm	0.8mm
X-ray Voltage/Current	-120 kV/2 mA	-120 kV/10 mA	-70 kV/1 mA
Detector	2000x2000 20 µm Screen / Microsc.	1000x1000 200 μm Direct Sci.	2000x1000 3/40 µm Screen/Imaging
Digital Resolution [Bits]	16	16	12
Sampling Time	500 ms-10 s	10 ms-1 s	5 s
Distance Object/Source	5-10 cm	10-50 cm	10-30 cm
Costs	1000 k€ (Zeiss)	500 k€(IFAM)	1 k€(Bosse)
Universität Bremen Fraunhofer			

12

TAXONOMY









Bremen





1. Aluminum Die Casting Plate (IFAM)

2. GLARE FML Plate (DFG FOR 3022)



DATA VARIANCE: THE FIRST CHALLENGE



In this work a semantic pixel classifier is used for feature marking. From the model point of view, each pixel (and neighbour pixels) of an X-ray image or volex of a CT image stack is a sample instance!

Universität Bremen Fraunhofer

METHODS AND ALGORITHMS

- Parametric 3D CAD modelling using automated model code generators, Monte Carlo simulation, and openSCAD
- X-ray simulation using own simulation software based on proven and accurate gvxr/gVirtualXray GPU library
- 3D CT reconstruction with Filtered Back Projection (using sine filters)
- Convolutional Neural Networks in different flavors (Damage/Defect Classifier)
- Anomaly detectors applied to images and CT volume data



X-RAY SIMULATION

- Input: Polygon mesh grid (STL, Stereolithography file format) model
 - An STL file describes a raw, unstructured triangulated surface
 - Decomposition of multi-material structures in single density parts (finally merged in simulator)
 - 3D Model design: Constructive Solid Geometry (CSG)
- Output: X-ray intensity image with a specific detector resolution (number of pixels) and pixel size, floating point or integer data format (at least 16 Bits)
- Spatial source, object, and detector geometries can be fully parametrized including rotatated planes
- Core software library: gvxr / gVirtualXray using GPU computations and the OpenGL Shading Language (faster than 1ms / image)
 - <u>https://gvirtualxray.fpvidal.net/</u>
 - Based on the Beer-Lambert law to compute the absorption of light (i.e. photons) by 3D objects (here polygon meshes).

Universität Bremen Fraunhofer

X-RAY SIMULATION: CAD MODEL USING CSG

rotate ([90,90,90]) difference () { rotate ([90,0,0]) cube([100,4,40],true); union () { translate([3.17,6.14,0.67]) **rotate** ([0,0,-1.43]) scale([1.15,1.12,0.31]) sphere(r=0.5,\$fn=20); translate([-16.66,-4.05,0.39]) **rotate** ([0,0,40.14]) scale([0.89,2.21,1.46]) sphere(r=0.5,\$fn=20);

Fraunhofer

IFAM

Universität

Bremen



Constructive

X-RAY SIMULATION

- C++ simulation library gvxr/gVirtualXray¹
- Integrated in own simulator program XraySim: <u>https://github.com/bslab/xraysim</u>
- GPU/OpenGL Ray tracing using Beer-Lambert law
- Absorption along direct transmission path from source to detector – no scattering and reflection!



¹ Simulation of X-ray projections on GPU: Benchmarking gVirtualXray with clinically realistic phantoms, Jamie Lea Pointon, Tianci Wen, Jenna Tugwell-Allsup, Aaron Sújar, Jean Michel Létang, and Franck Patrick Vidal Computer Methods and Programs in Biomedicine, 2023....

X-RAY SIMULATION: NOISE

We have different noise sources that have an impact on image quality and the predictions of data-driven models (noise sensitive FP artifacts):

- Gaussian Noise (Electronics, Detector)
- Poisson Noise (Quantum Effects in Detector and Scintillator)
- Positive Impulse Noise (Pop-corn noise due to X-ray radiation, Detector)
- Scattering Noise (Material)

💹 Fraunhofer

Universität

Bremen

Scintillator Noise (Static Inhom. Intensity)



SEMANTIC CNN PIXEL CLASSIFIER

- Input: A sub-window of an X-ray image
- **Output**: The object class to which the central pixel of the window belongs
- The CNN classifier is applied to all pixels of an input images and produces an equally sized feature marking output image
- Point clustering (e.g., using DBSCAN) can be used to extract list of geometric objects (pores, damages, ...)
- Supervised positive training (classification of known features classes)

💹 Fraunhofer

IFAM

Universität

Bremen



23

DAMAGE DETECTION IN FML CT DATA

Bremen

- Goal: Find (or mark) damages (deformations, cracks, delaminations) in 3D CT volumes
- Method: Z-Slicing of 3D CT volumes and application of a data-driven feature detector to z-profiled slices



DAMAGE DETECTION: POSITIVE VS. NEGATIVE TRAINING

Negative Training

The predictor model is trained with well known defects and damages (classifier). Suitable if there is a solid reference data set and an already existing knowledge base.

Positive Training

The predictor model is trained with the base-line reference without defects and damages (anomaly detector). Suitable to cover defects and damages with known and unknown characteristics.



ANOMALY DETECTION IN FML CT DATA: NEGATIVE TRAIN.

- An anomaly detector is build with a Autoencoder, either using a CNN or a LSTM-ANN
- The AE is trained with z-profile slices without defects or damages (base-line, ground truth data)
- The AE "learns" the z-profile structure of the FML plates and outputs a simplified representation (neg. Train.)
- If there is a damage/defect, the AE is not able to reconstruct the base-line structure, and an error occurs



Universität Bremen Fraunhofer

ANOMALY DETECTION IN FML CT DATA: NEGATIVE TRAIN.

• A CNN is trained with damaged z-profiles to classify damaged and undamged z-profile slices



Universität Bremen Fraunhofer

ANOMALY DETECTION IN FML CT DATA: SIMULATION

- A typical sample set contains less than 10 different specimens, each with a distinct and unique impact damage (and base-line = no damage)
- Data augmentation by simulation is required to increase feature and data variance!
- But in contrast to mechanical pore modeling in homogeneous materials, modeling of impact damages in FML is much more complicated reaching high accuracy (wrt. real structures and images)
- Hand-made layer boundary and damage polygon-marking using image tools → Time consuming!

Functional approximation \rightarrow Parametrizable 3D CAD model \rightarrow X-ray simulation

ANOMALY DETECTION IN FML CT DATA: SIMULATION



Universität Bremen Fraunhofer

FUSION OF REAL AND SYNTHETIC X-RAY IMAGES

- Modeling of specific material structures and image patterns can be a challenge:
 - Fibre Materials (Irregular, unknown geometric placement, clusters)

Bremen

- Non-Gaussian Correlated X-ray Noise (e.g., depends on X-ray tube & HV Supply)
- Solution: Modeling of target features (damages) and homogeneous materials + Overlay of real measured images (without defects, base-line)



RESULTS

- Convolutional Neural Networks applied to X-ray radiography images of Aluminum die casting plates
- Anomaly and damage detectors (CNN and LSTM-AE) applied to X-ray CT volume data



COMPARISON RECONSTRUCTED 3D CT (MID-Q) AND SINGLE PROJECTION X-RAY IMAGES (ALUDC)



- Left: Volume projection of reconstructed CT images with data from a Mid-Q device (400/800 projections, rec. with classical fbp alg.)
- Right: Single projection X-ray radiography images from same Mid-Q device

MID-Q RADIOGRAPHY AND CNN PORE FEATURE MARKING (R)



Right: CNN Pixel Classifier Feature Marking predicted from single projection image (MidQ), trained with real images [8-4]

Universität

Bremen

🗾 Fraunhofer

MID-Q RADIOGRAPHY AND CNN PORE FEATURE MARKING (S)



• Right: CNN Pixel Classifier Feature Marking predicted from single projection image (MidQ), trained with synthetic images [8-8-4]

Universität

Bremen

💹 Fraunhofer

LOW-Q RADIOGRAPHY AND CNN PORE FEATURE MARKING (S)



Left: Single projection X-ray radiography images from an Imaging LowQ device (M=1, eff. pixel size 40μm 1920x1080 pixels)

Universität

Bremen

🗾 Fraunhofer

IFAM

• Right: CNN Pixel Classifier Feature Marking predicted from single projection image (LowQ), trained with synthetic images [8-8-4]

LOW-Q RADIOGRAPHY AND CNN PORE FEATURE MARKING (S)



- Left: Single projection X-ray radiography images from an Imaging LowQ device // Rolled aluminum plate (d = 2 mm)
- Right: CNN Pixel Classifier Feature Marking predicted from single projection image (LowQ), trained with synthetic images [8-8-4]

SIMULATED RADIOGRAPHY AND CNN PORE FEATURE MARKING (GROUND TRUTH)



Left: Single projection X-ray radiography images from XraySim (M=2, pixel size 150µm 1000x1000 pixels, cropped) // Synthetic Plate

Right: CNN Pixel Classifier Feature Marking predicted from single projection image. 3 Layers [8-8-4]

Universität

Bremen

🗾 Fraunhofer



Left: Single projection X-ray radiography images from XraySim (M=2, pixel size 150µm 1000x1000 pixels, cropped) // Synthetic Plate

Right: CNN Pixel Classifier Feature Marking predicted from single projection image [8-8-4]

Universität

Bremen

💹 Fraunhofer

FML HOST MATERIAL AND DAMAGE MODELING

- Still work under progress
- Even the host material composite structure is a challenge
- Damages and Deformations must preserve material mass and volume!
- ROI and composite layer boundary marking with semiautomated tracker (and Canny edge detection)

Fraunhofer

IFAM

Universität

Bremen





ANOMALY DETECTION IN FML CT DATA (POSITIVE TRAIN.)



- A CNN is used to detect anomalies in a CT volume (feature marking of damage candidates) // Data from HighQ device
- Specimen: FML plate with different damages: A: foil pseudo defect,, B: Resin washout B, C: Baseline, D: Layer delamination:

1 Chirag Shah, Stefan Bosse, and Axel von Hehl. Taxonomy of Damage Patterns in Composite Materials, Measuring Signals, and Methods for Automated Damage Diagnostics, Materials 15 (MDPI), no. 13 (2022): 4645



ANOMALY DETECTION IN FML CT DATA (NEGATIVE TRAIN.)



- A LSTM Autoencoder is used as an anomaly detector. Shown is the feature marking of the AE (top view of the X.ray CT volume)
- Specimen: FML plate with impact damage. A-E: Different AE model configurations and trainings // Data from HighQ device

CONCLUSIONS

Data

- Single- and Multi-Proj. X-ray Images
- Data and feature variance is always limited!
- Supervised Learning: Handmade labeling is a challenge and inaccurate
 - Relation between image and target features can be very low (contrast)
- CT data can not be used directly for **labeling** due to geometrical distortions (wrt. single projection input data)

IFAM



Computer Science > Computer Vision and Pattern Recognition

[Submitted on 17 Nov 2023]

Automated Detection of hidden Damages and Impurities in Aluminum Die Casting Materials and Fibre-Metal Laminates using Low-quality X-ray Radiography, Synthetic X-ray Data Augmentation by Simulation, and Machine Learning

Stefan Bosse, Dirk Lehmhus

Methods

- **Convolutional Neural Networks** for pore and damage feature marling (data-driven negative training) and **LSTM** anomaly detectors (positive training)
- X-ray simulation based on Beer-Lambert law and multi-material polygon mesh models
- Monte Carlo simulation of materials with defects and damages (openSCAD, Constructive Solid Geometry)
- Measuring devices: Low-Q, Mid-Q, High-Q

Results

- A pure data-driven feature marking model (semantic image pixel classifier) trained with synthetic images only can be applied to real images
- The semantic pixel feature marling model is capable to highlight low-contrast features (e.g., hidden pores)
- X-ray noise has significant impact on feature prediction results
- Accurate and representative training examples (labelling, simulation models) are a prerequisite for robust data-driven models and a challenge!

THANK YOU

Stefan Bosse sbosse@uni-bremen.de www.edu-9.de







PORE INSPECTION AND CHARACTERISATION BY CT



It is a challenge to estimate pore shapes (geometry, size), density, spatial distribution, and to distinguish reconstructed pores from image artifcats and noise!

- Manual measuring of shape parameters of selected pores (e.g., using ImageJ analysis software) with ellipse approximation
- Automated pore analysis by point clustering methods and ellipsoid approximation





PORE INSPECTION AND CHARACTERISATION BY CT



It is a challenge to estimate pore shapes (geometry, size), density, spatial distribution, and to distinguish reconstructed pores from image artifcats and noise!

- Manual measuring of shape parameters of selected pores (e.g., using ImageJ analysis software) with ellipse approximation
- Automated pore analysis by point clustering methods and ellipsoid approximation





